

Br502

Top Mount Synthesized POCSAG Numeric Pager

Features

- Up to 18 personal memory slots
- Protect up to 10 messages
- Individual message delete or delete all
- Backlight
- Private time
- Daily alarm
- Time and date display
- Time and date message stamping
- Alert types: Melody, Chirp, Vibration, Vibration-chirp, Silent
- Battery low indicator and alert
- Out-of-range indicator and alert
- Unread message reminder alert
- Duplicate message indication
- Continuous message indication
- Error message indication
- Memory full indication
- Memory retention



Specifications

Model no:	Br502
Frequency:	VHF (135 - 175MHz), UHF (452 - 468MHz), 900MHz (929-932MHz)
Code Format:	31/21 POCSAG Code
Channel Spacing:	25 kHz
Frequency Deviation:	+/- 4.5 kHz
Paging Sensitivity:	-107 dBm (c.f. 22.5dB)
EIA Selectivity:	55 dB @ +/- 25 kHz 50 dB
EIA Spurious and Image:	50 dB 40 dB
IM Rejection:	50 dB 40 dB
Operating Temperature:	-10°C to 50°C 5°C to 40°C
Alert Tone Loudness:	75 dB @ 12 inches
Battery Type:	1 x Alkaline AAA
Weight (with battery):	45 grams
Dimensions:	64 x 43 x 19.5 mm

Contact Us

