

A new generation of pagers for today's professional.

BRAVO



BRAVO 501 POCSAG Numeric Pager

Features: 900 POCSAG

- Up to 12 Alerts
- 4 cap code capacity (any frame)
- Low Cell Alert
- Battery Gauge
- Programmable Power-Up Screen
- Stores up to 20 Personal Messages
- Message Time Stamping
- Shows Time and Date
- Built-In Alarm Clock
- Reminder Alert
- Delete Individual Messages or Erase All
- Backlight Display

Specifications: VHF/UHF/900 POCSAG

Model Number	VHF - 154-VPA, B, C, D, E
.....	UHF - 154-UPA, B, C, D
.....	900MHz - 154-9P
Frequency	VHF Synth. (135 - 174MHz)
.....	UHF Synth. (452 - 468MHz)
.....	900MHz Crystal (929 - 932MHz)
Code Format	POCSAG, 512/1200/2400 bps
Channel Spacing	25 kHz
Frequency deviation	+/- 4.5 kHz
Paging Sensitivity.....	5 mV/m for 512 bps
.....	7 mV/m for 1200 bps
.....	9 mV/m for 2400 bps
EIA Selectivity	55 dB
EIA Spurious and Image	50 dB
IM Rejection	50 dB
Operating Temp	-10°C to 50°C
Alert Tone Loudness.....	75 dB @ 12 inches
Battery Type	1 x Alkaline AAA
Battery Life	~35 days for 1200bps
.....	2 pages a day
Weight (with battery).....	45 grams
Size.....	.63 x .43 x 17.6 mm



BRAVO 501 