



USAlert, LLC

A Division of the Uni-Core Group

Receive the Information You Need with USAlert's NP-30 Numeric Pager

FEATURES:

NP-30

- Synthesized
Vibration, Tone, Melody and Silent
Alert
- 6 Individual Addresses
- Memory Capacity:
16 Messages, total 320 digits
- Unread Message Reminder
- Message Full Indicator
- Message Time Stamping
- Delete All/One Message
- Memory Backup (when replacing
battery)
- Out of Range Indicator
- Low Battery Alert & Indicator



Display:

- Large Screen Display
- Date and Time
- Backlight Display

NP-30 Traditional Pager

HIGH PERFORMANCE SPECIFICATIONS

USALERT'S TRADITIONAL PAGERS

NP30 VHF		NP30 UHF
A3B1AAA1213 (VHF)	Model Number	A4A1NPA2212 (UHF)
POCSAG	Protocol	POCSAG
138 - 167 MHz	Frequency MHz	450 - 470 MHz
0.0045% from 41°F to 104°F	Frequency Stability	0.0045% from 41°F to 104°F
25 KHz	Channel Spacing	25 KHz
5.0uV/m@512 bps	Sensitivity / Alerting	5.0uV/m@512 bps
512 / 1200 / 2400 bps	Transmission Speed	512 / 1200 / 2400 bps
55dB @ +/-25KHz	Adjacent Channel Selectivity	55dB @ +/-25KHz
FSK+/-4.5KHz	Modulation	FSK+/-4.5KHz
21.4MHz/455KHz	Intermediate Frequency	21.4MHz/455KHz
> 40 dB	Spurious Rejection	> 40 dB
> 40 dB	Image Rejection	> 40 dB
> 50 dB	Intermodulation Rejection	> 50 dB
>75db @ 30cm	Alert Response	>75dB @ 30cm
14°F to 131°F	Operating Temperature	14°F to 131°F
1 AA Alkaline	Battery Type	1 AA Alkaline
2.7"(L) X 2"(W) X 0.71"(H)	Dimensions	2.7"(L) X 2"(W) X 0.71"(H)
2.8 oz.	Weight	2.8 oz.

NP30 OPTIONS/ACCESSORIES

3 Year Warranty
 Cranberry Color Housing
 Teal Color Housing
 Programmer Kit
 User Guide
 White Boxes
 Alkaline Batteries

Provided By:

An authorized USAAlert Dealer/Distributor

